

Stainless steel free-standing letterbox designer model BIG ST-R with DoorBird video intercom - RAL of your choice

Product number 325B-VAR-K-KSDB2101E



Product description

Stainless steel free-standing letterbox designer model BIG ST-R with DoorBird D2100E or D1100E video intercom - RAL of your choice

High-quality, extra-large letterbox from Briefkasten Manufaktur. Integrated DoorBird IP video door station D2100E or D1100E. The DoorBird IP Video Door Station D2100E or D1100E is the smart solution for your entrance door. The IP video door station can be operated as a stand-alone unit or integrated into an existing smart home platform. Existing, classic installations such as a door chime or an electric door and gate opener can also continue to be used with DoorBird and controlled via the app.

This is a real eye-catcher among letterboxes. Clean lines and no-frills design characterise the designer letterbox. Our products have a high quality, reliable functionality and their own identity. Made by Briefkasten Manufaktur. The DoorBird was not only invented and developed in Germany, but is still produced in Berlin today. At DoorBird, "Made in Germany" is not just a seal, but a philosophy that is lived and breathed. The IP video door stations are manufactured in the DoorBird factory to guarantee the highest quality, durability and customer satisfaction.

- The letterbox is made of 2mm stainless steel V2A 1.4301, 240 grain polished, front panel powder-coated in RAL colour. Dimensions: height 750 mm; width: 450 mm; depth 100 mm.
- Front post removal door 350 mm x 300 mm, opens from top to bottom. Incl. 2 keys with key number.
- Mail slot from the front, dimensions: W 35 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without creasing.
- Front panel protrudes 2 cm all round.
- Optionally with house number, backlit in white incl. EVN LED power supply unit / transformer IP65 12V/DC 0.1-4W for LED illumination of the house number.
- The pedestals are made of 60.3 mm stainless steel V2A 1.4301, polished. Invisible cable routing through the pillars.
- Incl. DoorBird IP video door station D2100E or D1100E installed.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible. If you install this system completely free-standing, we recommend using a rain canopy. Tight-fitting self-adhesive rain cover enclosed.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. In certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Surface/colour	RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), Brushed, RAL 9007 grey aluminium, RAL 9016 traffic white
Series	DESIGNER
Connection technology	LAN
Number of bell push buttons	1 button
Functions	Newspaper compartment, Camera, Intercom, Fingerprint
Name labelling	Laser-cut engraving, Nameplate
Mounting type	Free-standing
Material	Stainless steel V2A 1.4301
House number	House number as laser cut, illuminated
Removal of mail	On the front
Number of boxes	with 1 letterbox
Boxes by volume	Large > 16 litres

Dimensions

Height of single box in mm	710,0 750,0
Width of single box in mm	410,0 450,0
Capacity in litres	21
Height of letterbox slot in mm	63,0
Width of letter slot in mm	350,0
Overall height in mm	1200,0 1500,0
Total width in mm	570,0
Depth in mm	100,0
Weight in kg	35
Delivery condition	Supplied in blocks, stand elements / letterbox divided

More images





