

# Design free-standing letterbox GRIMM ST-R - polished stainless steel - GIRA System 106 - Video intercom right- VIDEO complete set | Right | Gira System 106 complete set video | mail collection at the front | Stainless steel, ground

**Product number** 562-STR-SPR-1-VA-GI106KS



## Product description

### Design free-standing letterbox GRIMM® - A masterpiece of letterbox manufacturing

The GRIMM designer free-standing letterbox combines modern design with first-class workmanship - ideal for discerning building owners and architects who are looking for an elegant solution for integrating the Gira System 106. Manufactured from high-quality stainless steel and completely "Made in Germany" by the letterbox manufacturer Lippe, this model stands for durability, functionality and a stylish look. The polished front panel made of 2 mm stainless steel V2A (1.4301) impresses with its timeless appearance and high corrosion resistance. The flush-mounted design enables seamless integration of up to three GIRA 106 system modules via a sophisticated mounting system. 3 GIRA system modules are included, so the letterbox can be used directly. The matching GIRA home station and the control unit to complete this letterbox are included. The modules can be exchanged at any time thanks to the simple mounting system.

The freestanding GRIMM® letterbox is not only a visual highlight, but also at the forefront in terms of functionality and quality. Thanks to the innovative push-key lock, the letterbox can be operated easily and conveniently with one hand. Open the door with one push and close the door without using a key. The lock is optimally protected from the weather. The letterbox also offers an intelligent removal system: the door opens from top to bottom, ensuring that the mail remains securely in the box and cannot fall towards you. Mail is also conveniently inserted from the front, with high-quality axle dampers ensuring that the flap closes gently. The GRIMM is particularly unique thanks to its double box system: the body made of polished stainless steel V2A (\_\_\_\_00\_0\_\_) is installed first, while the cover can be inserted once the installation work is complete. The offset cover also offers optimum protection against rain and other environmental influences.

Thanks to the DIN/EN 13724 standard, the GRIMM is ideal for large letters in C4 format, which can be inserted without creasing. The GRIMM® letterbox impresses with its durable quality, timeless design and sophisticated functionality.

- High-quality free-standing letterbox made entirely of stainless steel.
- Front panel made of 2 mm stainless steel V2A 1.4301, polished.
- Quality production - Made in Germany by Briefkasten Manufaktur Lippe.
- Incl. GIRA home station & control unit enclosed, System 106 door station module, info module & camera module installed.
- Innovative push-key lock including 2 keys with key number, convenient locking without key, optimally protected from the weather.
- The removal door with opening limiter opens from top to bottom to prevent mail from falling towards you.
- Front mail slot with high-quality axle dampers for very quiet mail insertion.
- DIN/EN 13724-compliant letterbox, insertion size (3.5 cm x 32.5 cm) for C4 landscape - even large letters remain intact. Additional stainless steel removal protection integrated.
- Optimum weather protection thanks to offset cover.
- The pedestals are made of 60.3 mm stainless steel V2A 1.4301, polished for screw mounting or setting in concrete.

GIRA not found or type unknown

Camera module Gira System 106 - 5561 000

- A high-quality camera with high light sensitivity is concealed behind the replaceable black glass pane. Thanks to a detection angle of 100°, the user is always in the picture of what is happening outside his front door.

#### Info module Gira System 106 - 5560 920

- For house numbers that need to be clearly visible.

#### Door station module Gira System 106 - 5565 920

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with power via the door station module.

#### Surface-mounted home station Gira Video 7 1209xx

- Video home station with a 17.78 cm (7") TFT colour display and convenient hands-free function for surface mounting or wall mounting with flush-mounted device box or cavity wall box. Also suitable for placement on furniture with the optional stand (see accessories). A 32 GB SD memory card is included for internal image storage. Full-surface glass front with touch functionality and tactile feedback.

#### Video REG control device Gira 128800

- Control device for supplying the audio and video components of the Gira door communication bus.
- Supply of the reverse-polarity protected and short-circuit-proof 2-wire bus when using video components such as colour camera, TFT colour display.
- Up to 2 door stations with colour camera and 28 home stations with TFT colour display can be supplied via the video control device.
- A total of up to 15 colour cameras can be controlled by the video control device (5 video door stations and 10 DCS camera gateways), of which two door stations with colour camera can be supplied with power by the video control device. The other colour cameras must each be operated with their own power supply for door communication.
- Self-resetting electronic short-circuit and overload detection of the operating voltages and the bus connection.
- Buttons for system and door release programming.
- LED status indicators for operation, overload, system programming and door opener programming.
- AC 12 V output for supplying power to a standard electric strike.
- Relay output for switching an electric strike with its own power supply.
- Door opener switching time continuously adjustable from 1 to 10 s.

#### Important information:

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is completely placed in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

## Product properties

<b>Series</b>	GRIMM
<b>Connection technology</b>	2-wire
<b>Number of bell push buttons</b>	1 button
<b>Functions</b>	Camera, Intercom
<b>Mounting type</b>	Free-standing
<b>Material</b>	Stainless steel V2A 1.4301, Stainless steel 1.4016 (non-rusting magnetic stainless steel)
<b>House number</b>	House number as laser cut, illuminated
<b>Name labelling</b>	Laser-engraved
<b>Removal of mail</b>	On the front
<b>Number of boxes</b>	with 1 letterbox
<b>Surface/colour</b>	Brushed
<b>Boxes by volume</b>	Large > 16 litres

## Dimensions

<b>Height of single box in mm</b>	460,0
<b>Width of single box in mm</b>	610,0
<b>Capacity in litres</b>	26,0
<b>Height of letterbox slot in mm</b>	35,0
<b>Width of letter slot in mm</b>	325,0
<b>Height of letterbox in mm</b>	510,0
<b>Width of letterbox system in mm</b>	610,0
<b>Overall height in mm</b>	1200,0   1500,0   1700,0 +30
<b>Total width in mm</b>	610,0
<b>Depth in mm</b>	150,0
<b>Weight in kg</b>	41
<b>Delivery condition</b>	Supplied in blocks, stand elements / letterbox divided

## More images



