

# Video door station free-standing DIVISION 530S ST-Q - RAL of your choice - Comelit Ultra VIDEO Set

Product number 530S-E-STQ-KSCSWIFI-1



### Product description

# Video door station free-standing DIVISION 530S ST-Q - RAL of your choice - Comelit VIDEO Set

The free-standing DIVISION 530S video intercom is the perfect combination of state-of-the-art door communication, high-quality design and maximum ease of use. The elegant front made of powder-coated stainless steel in the colour of your choice blends seamlessly into any building façade, while the white illuminated bell push sets a stylish accent. The high-quality finish in V2A stainless steel makes the system particularly robust, durable and weather-resistant - ideal for long-term outdoor use.

Equipped with the innovative Comelit camera, you can experience razor-sharp live images, a generous wide angle, face recognition and voice control. Convenient operation via mobile phone or indoor intercom: Using the free Comelit app, you can receive visitor calls directly on your smartphone, see the camera image in real time, speak to guests and even open doors or gates if you wish - no matter where you are.

With the DIVISION 530S video call station, you are opting for a flexible, modular system in which front panels and camera modules can be easily replaced even years later. This means your door communication is always up to date - both technically and visually.

- Free-standing door station made of 2 mm stainless steel V2A 1.4301.
- Interchangeable front panels powder-coated in RAL colour of your choice.
- Installation box made of 2 mm stainless steel V2A 1.4301, 240 grit polished.
- 8-12V DC short-stroke bell push-button with LED ring lighting in white.
- Doorbell plate dimensions: W 160 mm x H 260 mm x D 8 mm.
- Installation box dimensions: W 130 mm x H 230 mm x D 50 mm.
- The pedestals are made of 40 mm x 40 mm stainless steel V2A 1.4301, powder-coated in RAL colour for setting in concrete or screw mounting.

#### Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

To achieve optimum water protection, the door station should be located under a canopy if possible.



## **Product properties**

Surface/colour RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your

choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white

Series DIVISION
Connection 2-wire

technology

Number of bell push 1 button

buttons Functions

Camera, Intercom

Mounting type Free-standing

Material Stainless steel V2A 1.4301

House number as laser engraving

Name labelling Laser-engraved

#### **Dimensions**

 Width in mm
 130 | 160

 Height in mm
 230 | 260

Overall height in mm 1200.0 | 1500.0 | 1700.0 (recommended camera height 1400.0 -1600.0)

Total width in mm 210,0 Depth in mm 52,0 Weight in kg 4

**Delivery condition** Supplied in blocks, floor units/door station divided



# More images













