

3 x 2 stainless steel flush-mounted letterbox system BASIC Plus 382XU UP with bell box - RAL of your choice | Left | 150mm depth | ? Colour of your choice | with 3 letterboxes (2x2)

Product number 382XU-3-SP-L-150



Product description

3 x 2 stainless steel flush-mounted letterbox system BASIC Plus 382XU UP - RAL of your choice - 3 parties

Modern flush-mounted letterbox for 3 parties - made in Germany by Briefkasten Manufaktur.

The letterbox is made entirely of stainless steel V2A, powder-coated in RAL colour. The very high-quality workmanship and the well thought-out concept make this flush-mounted letterbox our top seller. A rain drainage edge for optimum water protection, a continuous rubber lip for quiet insertion, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this flush-mounted letterbox. The flush-mounted frame made of V2A stainless steel is fitted with a foam rubber seal and guarantees a very long service life.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- **3-gang flush-mounted letterbox system made entirely of stainless steel V2A 1.4301, powder-coated in RAL colour**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with sound-absorbing rubber seal for very quiet mail insertion.
- The door can be opened from left to right.
- Incl. 2 keys with key number, interchangeable nameplate (type 2) under the flap and post holder.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- **Bell box made of stainless steel V2A 1.4301, powder-coated in RAL colour fine structure matt**
- Speech perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in the scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 3x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate (type 1) is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, powder-coated in RAL colour.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Surface/colour	RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white
Series	BASIC
Number of bell push buttons	3 buttons
Functions	Light button, Intercom
Functional box prepared for manufacturer	GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald, Legrand Bticino, Comelit
Name labelling	Nameplate
Material	Stainless steel V2A 1.4301
Removal of mail	On the front
Boxes by volume	Large > 16 litres
Number of boxes	with 3 letterboxes
Mounting type	Flush-mounted

Dimensions

Height of single box in mm	330,0
Width of single box in mm	355,0
Capacity in litres	12,0 17,0
Height of letterbox slot in mm	35,0
Width of letter slot in mm	325,0
Height of letterbox in mm	710,0
Width of letterbox system in mm	760,0
Depth in mm	100,0 150,0
Weight in kg	32
Delivery condition	Supplied fully assembled

More images



