

1 surface-mounted letterbox system Design BASIC 385A-VA surface-mounted with bell box - stainless steel V2A, polished | Top | Stainless steel, ground | with 1 letterbox

Product number 385A-VA-1-SP



Product description

Surface-mounted letterbox system Design BASIC 385A-VA-SP made of stainless steel V2 A polished with bell box incl. side panelling & rain cover

Modern surface-mounted letterbox made in Germany by Briefkasten Manufaktur.

The letterboxes are made of weather-resistant V2A stainless steel, polished. The very high-quality workmanship and the sophisticated concept make this letterbox system our top seller. This letterbox system is characterised by close-fitting side cladding with a rain canopy and the rain drainage channels for optimum water protection, a throw-in flap with rubber lip, the solid interchangeable nameplate and the robust lock.

Thanks to the design, self-assembly is uncomplicated.

- Surface-mounted letterbox made of stainless steel V2 A, polished
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 26.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber lip for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number and changeable name plate under the flap.
- Optionally available with close-fitting side panelling + rain cover made of V2A stainless steel, polished.
- Bell box made of stainless steel V2 A, polished
- Intercom hole with universal adapter. (Intercom system/ built-in loudspeaker not included in the scope of delivery).
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push type 4, max. 250 V AC, 5 A.
- Anti-vandalism The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- For simple 1-2 person wall mounting with mounting rail incl. fixing material (screws + wall plugs).

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water may still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.



Product properties

Series BASIC
Number of bell push buttons 1 button

Functions Light button, Intercom

Functional box prepared for GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner,

manufacturer Auerswald, Legrand Bticino, Comelit

Boxes by volume Normal > 10 litres

Name labelling Nameplate

Material Stainless steel V2A 1.4301

Removal of mail On the front

Number of boxes with 1 letterbox

Surface/colour Brushed

Mounting type Surface-mounted


Dimensions


Height of single box in mm 110,0 Width of single box in mm 300.0 Capacity in litres 12 Height of letterbox slot in mm 35,0 Width of letter slot in mm 265,0 Height of letterbox in mm 220,0 Width of letterbox system in mm 300,0 435,0 Depth in mm Weight in kg

Delivery condition Supplied fully assembled



Drawing







More images





