

# Gira System 106 surface-mounted housing, 3-gang - anthracite 5503910 | 3-way | Anthracite



**Product number** S106-5503910

## Product description

### Gira System 106 surface-mounted housing, 3-gang - anthracite

Very low installation height of 28.4 mm. Vertical and horizontal mounting (only for 2-gang, 3-gang, 4-gang and 5-gang surface-mounted housing) enables optimum adaptation to the installation location. Suitable for use on facades with a thermal insulation composite system.

Ribbon cable, 10-pole and terminating resistors are included in the scope of delivery (exception: 1-gang surface-mounted housing).

The Gira System 106 is an installation system made of real metal in a purist, elegant design without a frame, based on a basic dimension of 106.5 × 106.5 mm. With the modular door station in the Gira System 106, hospitality begins at the front door. From the call button, voice and camera module to the info and blind module, all functions are presented in a harmonious overall picture. In the dark, the backlit call buttons with labelling field ensure good legibility and an attractive appearance.

System 106 can be used in detached houses and apartment blocks, as well as in office buildings, industrial premises and hotels. The modular structure allows the system to be customised in size, design and functionality to suit individual requirements. Extensions and changes can be easily made at any time by exchanging modules. Even a pure front change is possible with the system. This means that the appearance of the system can be subsequently changed from, for example, traffic white to a stainless steel finish without having to replace the electronic units.

#### Simple installation and step-by-step assembly

The system can be installed in various stages in parallel with the construction progress. For example, it is possible to install only the lower part of the surface-mounted housing during the shell construction phase, and then add cables and modules as and when they are needed.

## Product properties

**Mounting type** Surface-mounted

## Dimensions

**Width in mm** 106,5

**Height in mm** 106,5

**Depth in mm** 25,4

**Weight in kg** 0,5

## More images

