

GOETHE MDW design letterbox - RAL of your choice - DoorBird video intercom system | 300-390mm depth

Product number 215-MDW-1-SP-DB-390



Product description

GOETHE MDW design flush-mounted letterbox - RAL of your choice - DoorBird video intercom system

The modern GOETHE wall letterbox with a seamlessly integrated DoorBird IP Video Door Station D2100E or D1100E in a flush-mounted design. The DoorBird IP Video Door Station D2100E or D1100E is the smart solution for your entrance door. The IP video door station can be operated as a stand-alone unit or integrated into an existing smart home platform. Existing, classic installations such as a door chime or an electric door and gate opener can also continue to be used with DoorBird and controlled via the app.

Thanks to the variable shaft length of between 300mm and 390mm or 390mm and 560mm, this letterbox can be installed in almost all types of masonry.

The dimensions of the individual boxes allow a capacity of approx. 24-44 litres, and the large slot guarantees no crumpled mail, even with DIN C4 envelopes and magazines or after several days of absence. Thanks to the water drainage edge, the mail inside is optimally protected from the weather. The insertion flap is fitted with high-quality axle dampers, guaranteeing quiet closing and preventing annoying rattling caused by the weather.

The letterbox systems in the GOETHE collection are characterised by the consistent use of stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are available directly in our shop.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5



- High-quality, stainless steel letterbox.
- Shaft made of 1.4016 stainless steel (magnetic stainless steel), bright.
- Body made of stainless steel 1.4016 (stainless magnetic stainless steel), powder-coated in RAL colour of your choice.
- Quality production Made in Germany by Briefkasten Manufaktur Lippe.
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 landscape, large letters also fit in here without creasing.
- Letter slot & removal door made of stainless steel V2A 1.4301, powder-coated in RAL colour of your choice.
- Letters are inserted and removed from the front. Insertion flap with high-quality axle dampers for very quiet mail insertion.
- Removal door opens from top to bottom. This prevents the mail from falling towards you.
- Functional box (BH 400x200mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL colour of your choice.
- Optionally with house number and name inscription, lasered.
- Incl. DoorBird IP video door station D2100E or D1100E installed.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, powder-coated in RAL colour.
- Variable shaft length 300-390mm or 390-560mm. External dimensions of letter slot W 380 mm x H 180 mm.
- External dimensions front W 450mm x H 650mm; rear W 450mm x H 250mm.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Product properties

Surface/colour RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of

your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white

Series GOETHE Connection technology LAN Number of bell push 1 button

buttons

Functions Camera, Intercom, Fingerprint, Keypad

Functional box prepared for DoorBird

manufacturer

Material Aluminium AlMg3 W19, Stainless steel V2A 1.4301, Stainless steel 1.4016 (non-rusting magnetic

stainless steel)

House number House number as laser engraving, House number as laser cut, illuminated

Laser-engraved, Illuminated laser-cut engraving Name labelling

Number of boxes with 1 letterbox Boxes by volume Large > 16 litres Mounting type Wall throw-through Removal of mail On the back

Briefkasten Manufaktur Lippe GmbH Werler Straße 60 32105 Bad Salzuflen

www.briefkasten-manufaktur.de info@briefkasten-manufaktur.de Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck Ust.ID.Nr. DE303690847 Handelsregister Amtsgericht Lemgo, HRB 8618



Dimensions

Height of single box in mm BK 200.0 | FK 400.0

Width of single box in mm 400,0

Capacity in litres 24,0 - 32,0 | 32,0 - 44,0

Height of letterbox slot in mm 35,0 Width of letter slot in mm 360,0

Overall height in mm recommended 1500.0 - 1700.0

Total width in mm 450,0


Depth in mm BK 300.0 - 390.0 | BK 390.0 - 560.0 | FK 100.0


Weight in kg 24

Delivery condition Supplied partially disassembled



Drawing







More images





