

3er 1x3 stainless steel surface-mounted letterbox design BASIC Plus 382XA AP - RAL of your choice | 100mm depth | ? Colour of your choice | with 3 letterboxes (3x1) | Close-fitting cladding with mounting rail

Product number 382XA-3W-100



Product description

3er 1x3 stainless steel surface-mounted letterbox design BASIC Plus 382XA AP - RAL of your choice

High-quality surface-mounted letterbox for 3 parties made in Germany by Briefkasten Manufaktur.

The complete surface-mounted letterbox system is made of stainless steel V2A, powder-coated in RAL colour. The very high-quality workmanship and the well thought-out concept make this letterbox system our top seller. A rain drainage edge for optimum water protection, a continuous rubber lip for quiet insertion, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this surface-mounted letterbox system.

Thanks to the design, self-assembly is straightforward. The letterbox system is prepared for uncomplicated complete installation, so there is no need for time-consuming wall mounting of individual boxes.

- 3-box surface-mounted letterbox system with letterboxes made of stainless steel V2A, powder-coated in RAL colour.
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber seal for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder for each letterbox.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- Incl. side cladding + rain cover made of V2A stainless steel, powder-coated in RAL colour.
- For wall mounting incl. mounting rail and fixing material (screws + dowels).

Important information:

The post is only protected from moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Surface/colour	RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white
Series	BASIC
Boxes by volume	Normal > 10 litres
Name labelling	Nameplate
Material	Stainless steel V2A 1.4301
Removal of mail	On the front
Mounting type	Surface-mounted
Number of boxes	with 3 letterboxes

Dimensions

Height of single box in mm	330,0
Width of single box in mm	355,0
Capacity in litres	12,0 17,0
Height of letterbox slot in mm	35,0
Width of letter slot in mm	325,0
Height of letterbox in mm	330,0
Width of letterbox system in mm	1065,0
Depth in mm	100,0 150,0
Weight in kg	36
Delivery condition	System is delivered pre-assembled/partially disassembled

More images



