

# 12 pcs 3x4 surface-mounted letterbox system Design BASIC 382 AP - stainless steel RAL 7016 anthracite grey | 100mm depth | Bi-colour polished stainless steel | RAL 7016 anthracite grey | Battery assembly (without roof and cladding) | with 12 letterboxes (3x4)

**Product number** 382A-7016VA-12S-100



## Product description

### 12-point 3x4 surface-mounted letterbox system Design BASIC 382A-7016VA - Vertical - Stainless steel anthracite grey RAL 7016

High-quality surface-mounted letterbox for 12 parties made in Germany by Briefkasten Manufaktur.

The surface-mounted letterbox system is made of galvanised steel, powder-coated in RAL 7016 anthracite grey fine structure matt, the flap is made of weather-resistant stainless steel V2A, polished. The very high-quality workmanship and the well thought-out concept make this letterbox system our top seller. This surface-mounted letterbox system is characterised by a rain drainage edge for optimum water protection, a double-edged throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock.

Thanks to the design, self-assembly is straightforward.

- 12-point surface-mounted letterbox system with letterboxes made of galvanised sheet steel, powder-coated in RAL anthracite grey 7016 fine structure.
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Stainless steel insertion flaps, polished with noise-absorbing rubber buffers for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder for each letterbox.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- For wall mounting incl. fixing material (screws + wall plugs).

#### Important information:

The mail is only protected from moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## Product properties

<b>Material</b>	Steel, galvanised, Stainless steel V2A 1.4301
<b>Series</b>	BASIC
<b>Boxes by volume</b>	Normal > 10 litres
<b>Name labelling</b>	Nameplate
<b>Surface/colour</b>	RAL 7016 anthracite grey, Brushed
<b>Removal of mail</b>	On the front
<b>Mounting type</b>	Surface-mounted
<b>Number of boxes</b>	with 12 letterboxes

## Dimensions

<b>Height of single box in mm</b>	330,0
<b>Width of single box in mm</b>	355,0
<b>Capacity in litres</b>	12,0   17,0
<b>Height of letterbox slot in mm</b>	35,0
<b>Width of letter slot in mm</b>	325,0
<b>Height of letterbox in mm</b>	1320,0
<b>Width of letterbox system in mm</b>	1065,0
<b>Depth in mm</b>	100,0   150,0
<b>Weight in kg</b>	66
<b>Delivery condition</b>	System is delivered pre-assembled/partially disassembled

## More images

