

3-piece stainless steel surface-mounted letterbox design BASIC Plus 382XA AP with bell box - stainless steel V2A | Left | 150mm depth | with 3 letterboxes (2x2) | Stainless steel, ground

Product number 382XA-VA-3S-SP-150-L



Product description

3er 2x2 stainless steel surface-mounted letterbox design BASIC Plus 382XA AP with bell box - stainless steel V2A

High-quality surface-mounted letterbox for 3 parties made in Germany by Briefkasten Manufaktur.

The complete surface-mounted letterbox system is made of V2A stainless steel, polished. The very high-quality workmanship and the well thought-out concept make this letterbox system our top seller. A rain drainage edge for optimum water protection, a continuous rubber lip for quiet insertion, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this surface-mounted letterbox system.

Thanks to the design, self-assembly is straightforward. The letterbox system is prepared for uncomplicated complete installation, so there is no need for time-consuming wall mounting of individual boxes.

- 3-box surface-mounted letterbox system made entirely of stainless steel V2A 1.4301, polished.
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber seal for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder for each letterbox.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- Incl. side panelling + rain cover made of V2A stainless steel, polished.
- For wall mounting incl. mounting rail and fixing material (screws + dowels).

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water may still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Series	BASIC
Number of bell push buttons	1 button, 2 buttons, 3 buttons
Functions	Light button, Intercom
Functional box prepared for manufacturer	GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald, Legrand Bticino, Comelit
Name labelling	Nameplate
Material	Stainless steel V2A 1.4301
Removal of mail	On the front
Surface/colour	Brushed
Boxes by volume	Large > 16 litres
Mounting type	Surface-mounted
Number of letterboxes	with 3 letterboxes

Dimensions

Height of single box in mm	330,0
Width of single box in mm	355,0
Capacity in litres	12,0 17,0
Height of letterbox slot in mm	35,0
Width of letter slot in mm	325,0
Height of letterbox in mm	660,0
Width of letterbox system in mm	710,0
Depth in mm	100,0 150,0
Weight in kg	21
Delivery condition	Delivery is pre-assembled/partially disassembled

More images





