

# 5-piece 2x3 stainless steel flush-mounted letterbox system BASIC Plus 382XU UP with bell box | Right | 150mm depth | with 5 letterboxes (2x3) | Stainless steel, ground

Product number 382XU-VA-5S-SP-R-150



### **Product description**

# 5er 2x3 stainless steel flush-mounted letterbox system BASIC Plus 382XU UP - polished stainless steel - 5 parties

Modern flush-mounted letterbox for 5 parties - made in Germany by Briefkasten Manufaktur.

The letterbox is made entirely of polished V2A stainless steel. The very high-quality workmanship and the well thought-out concept make this flush-mounted letter box our top seller. A rain drainage edge for optimum water protection, a continuous rubber lip for quiet insertion, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this flush-mounted letterbox. The flush-mounted frame made of V2A stainless steel is fitted with a foam rubber seal and guarantees a very long service life.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- 5-fold flush-mounted letterbox system made entirely of stainless steel V2A 1.4301, 240 grain polished
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with sound-absorbing rubber seal for very quiet mail insertion.
- The door can be opened from left to right.
- Incl. 2 keys with key number, interchangeable nameplate (type 2) under the flap and post holder.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- Bell box made of stainless steel V2A 1.4301, 240 grain polished
- Speech perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in the scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 5x round stainless steel bell push-buttons type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism The nameplate (type 1) is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, 240 grain polished.

#### Important information

Camera or intercom preparation



The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

#### Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## **Product properties**

**BASIC Series** Number of bell push buttons 5 buttons

**Functions** Light button, Intercom

Functional box prepared for GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner,

manufacturer Auerswald, Legrand Bticino, Comelit

Name labelling Nameplate

Material Stainless steel V2A 1.4301

Removal of mail On the front Number of boxes with 5 letterboxes

Surface/colour Brushed

Boxes by volume Large > 16 litres Mounting type Flush-mounted

#### **Dimensions**

Height of single box in mm 330,0 Width of single box in mm 355,0 Capacity in litres 12,0 | 17,0 Height of letterbox slot in mm 35,0 Width of letter slot in mm 325,0 Height of letterbox in mm 1040,0 Width of letterbox system in mm 760,0

Depth in mm 100,0 | 150,0

Weight in kg

**Delivery condition** Supplied fully assembled



# More images















