

# Set of 3 GIRA System 106 - Stainless steel V2A - Intercom with 1x bell push-button | Stainless steel, ground

**Product number** S106-KS3A1-VA



## Product description

### Set of 3 GIRA System 106 - Stainless steel V2A - Intercom system with 1x bell button

Gira System 106 made of V2A stainless steel in flush-mounted design for use in the DESIGNER 3-gang letterboxes or for simple surface mounting on the wall. 3 GIRA system modules and surface-mounted housing are included, so the system can be used directly in the letterbox. The system modules can be subsequently replaced as required thanks to the simple mounting system. The matching GIRA home station and control unit are available under accessories.

#### Surface-mounted housing 3gang Gira System 106 - 5503 910

- For flush-mounted installation of the modules.

#### 2x info module Gira System 106 - 5560 920

- For house numbers and name labelling that should be clearly visible.

#### Door station module Gira System 106 - 5569 920 + call button 5549 920

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with power via the door station module.

Additional components required. See accessories!

- Gira surface-mounted home station 1250xx
- Gira audio REG control device 128700

## Important information

### Camera or intercom preparation

**The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, fitting and installation.**

### Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## Product properties

<b>Connection technology</b>	2-wire
<b>Material</b>	Stainless steel V2A 1.4301
<b>Surface/colour</b>	Brushed

## Dimensions

<b>Width in mm</b>	320
<b>Height in mm</b>	106
<b>Depth in mm</b>	20,0

## More images

