

# Pedestal letterbox design BASIC 381 ST-R with bell box & newspaper compartment - RAL 7016 anthracite grey | RAL 7016 anthracite grey, fine structure, matt | with 1 letterbox

Product number 381-K7016-1-SP-ZF



## Product description

### Free-standing letter box, design BASIC 381 - anthracite grey RAL 7016 with bell box & newspaper tube

Modern free-standing letter box made in Germany by Briefkasten Manufaktur.

The letterbox is made of galvanised steel, powder-coated in RAL colour fine structure matt, the stand elements are made of weather-resistant stainless steel V2A, polished. The very high-quality workmanship and the well thought-out concept make this free-standing letterbox our top seller. A rain drainage edge for optimum water protection, a continuous rubber lip for quiet insertion, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this free-standing letterbox. This letterbox is easy to clean and robust.

Thanks to the design, self-assembly is uncomplicated.

- **Standing letterbox made of galvanised steel, powder-coated in RAL colour fine structure matt**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber seal for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder for each letterbox.
- Newspaper compartment, open on both sides, made of stainless steel V2A, powder-coated in RAL colour fine structure matt. Dimensions: 355x100x100mm.
- Incl. side panelling + rain cover in solid design.
- **Doorbell box made of galvanised steel, powder-coated in RAL colour fine structure matt**
- Speech perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Cable access: Ø 10.4 mm (on the right side). Invisible cable routing through the stand element.
- The stand elements are made of 42.4 mm V2A stainless steel 1.4301, polished for screw mounting or setting in concrete.

## Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

#### Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## Product properties



<b>Material</b>	Steel, galvanised, Stainless steel V2A 1.4301
<b>Series</b>	BASIC
<b>Number of bell push buttons</b>	1 button, 2 buttons, 3 buttons
<b>Functions</b>	Newspaper compartment, Light button, Camera, Intercom
<b>Functional box prepared for manufacturer</b>	GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald, Legrand Bticino, Comelit
<b>Boxes by volume</b>	Normal > 10 litres
<b>Name labelling</b>	Nameplate
<b>Mounting type</b>	Free-standing
<b>House number</b>	House number as laser engraving
<b>Surface/colour</b>	RAL 7016 anthracite grey, Brushed
<b>Removal of mail</b>	On the front
<b>Number of boxes</b>	with 1 letterbox

## Dimensions

<b>Height of single box in mm</b>	330,0
<b>Width of single box in mm</b>	355,0
<b>Capacity in litres</b>	12
<b>Height of letterbox slot in mm</b>	35,0
<b>Width of letter slot in mm</b>	325,0
<b>Height of letterbox in mm</b>	530,0
<b>Width of letterbox system in mm</b>	355,0
<b>Overall height in mm</b>	1200.0   1500.0 + 70.0 Attached rain roof
<b>Total width in mm</b>	535,0
<b>Depth in mm</b>	100,0
<b>Weight in kg</b>	21
<b>Delivery condition</b>	Supplied in blocks, stand elements / letterbox divided

## Drawing

Montagebohrungen



## More images

