

# DoorBird IP VIDEO home station A1101 | Black

**Product number** 1298-A1101-BL



## Product description

### DoorBird IP VIDEO Home Station A1101 Black Edition

The DoorBird IP Video indoor station is the ideal addition to any letterbox with DoorBird IP Video door station. It is characterised by outstanding video and audio quality. The compact and discreet design harmonises with any environment. The screen of the indoor station is made of scratch-resistant safety glass. The intuitive user interface with clear icons means that all functions can be accessed in seconds. All main functions can be called up using the hardware buttons - without using the touchscreen.

The customised ringtone for the front door, floor or gate allows you to distinguish exactly where the visitor is ringing. The LED status bar on the underside of the indoor station lights up in freely selectable colours.

#### **Added value through IP**

- Door opening and lift call
- Visitor history (free cloud recording)
- Weather forecast
- Home and building automation control (IP, TCP, HTTPS, relay, etc.)
- Configuration worldwide via the DoorBird app

#### **Intuitive user interface**

- 4-inch true colour touch display
- Scratch-resistant Gorilla® safety glass

#### **2-way audio**

- HD audio, up to 102 dB
- Over 50 ringtones

#### **Compact housing**

- 5 hardware buttons for the main functions
- Configurable RGB LED status bar

#### **Unlimited range**

- Supports WLAN, Ethernet, PoE
- Suitable for multiple DoorBird IP video door stations

## TECHNICAL DATA

**Surface-mounted**, table stand A8003 available separately

**Power supply** 15 - 48 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)

**Weight** 336 g

**Connections**

- LAN/PoE (T+, T-, R+, R-)
- Digital input #1 (0 V, 0 A (NO)), e.g. for a storey call button
- Digital input #2, (0 V, 0 A (NO)), e.g. for a second storey call button
- Bi-stable latching switching relay #1, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- Bi-stable latching switching relay #2, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- Bi-stable latching switching relay #3, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- 15 - 48 V DC input (+, -), max. 15 W Power consumption 5 W

**Approvals** CE, FCC, IC, RoHS, IP50

**Operating conditions** 0 to +55°C / 32 to 131°F

**Relative humidity** 0 % to 85 % (non-condensing)

**SYSTEM REQUIREMENTS**

**Mobile device** Latest iOS on iPhone/iPad, latest Android on smartphone/tablet

**Internet** High-speed fixed network Broadband Internet connection, DSL, cable or fibre optic, no sockets or proxy server

**Network** Ethernet network, with DHCP

**Supported door stations** Any DoorBird IP video door station

**DISPLAY**

**Dimensions** 4" true colour LCD

**Touch** Yes, capacitive

**Resolution** 800 x 480 px

**IPS** Yes

**AUDIO**

**Audio components** Speaker and microphone, echo and noise cancellation (AEC, ANR)

**Audio streaming** two-way

**NETWORK**

**Ethernet** PoE 802.3af Mode-A

**WLAN** 802.11 b/g/n 2.4 GHz

**INTEGRATED RADIO MODULES**

**WLAN** 802.11 b/g/n 2.4 GHz

**Important information**

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

**Dimensions**

**Width in mm** 115

**Height in mm** 185

**Depth in mm** 25,0

**Weight in kg** 0,4

## More images

