

Design letterbox pedestal GOETHE with newspaper compartment - RAL of your choice - LOXONE Intercom/Code Touch prepared | 2x1 LOXONE intercom + code touch/touch prepared

Product number 215-STL-160-1ZFS-LX-LOX2H



Product description

Design letterbox pedestal GOETHE with newspaper compartment - RAL of your choice - LOXONE Intercom/Code Touch prepared

High-quality letterbox pedestal with newspaper compartment in flush-mounted design. The modern GOETHE letterbox is ideal for the sophisticated entrance area. The linear design without a visible lock makes this letterbox look particularly elegant. The LOXONE Intercom can be seamlessly integrated into the flush-mounted design and replaced at any time. The preparation is intended for 1 piece LOXONE Intercom (incl. perforation for sound outlet) or 1 piece LOXONE Intercom (incl. perforation for sound outlet) + 1 piece LOXONE NFC Code Touch/Touch Pure.

The dimensions of the single box allow a capacity of approx. 16 litres, the large slot guarantees no crumpled mail even with DIN C4 envelopes and magazines or after several days of absence. The innovative push-key lock is concealed inside the letterbox. The key is simply inserted into the existing opening (no turning required) and the door opens. With the arrangement of the lock, this letterbox is designed in such a way that the removal door prevents the mail from falling towards you. The water drainage edge ensures that the mail inside is optimally protected from the weather. The insertion flap is fitted with high-quality axle dampers, guaranteeing quiet closing and preventing annoying rattling caused by the weather.

The letterbox systems in the GOETHE collection are characterised by the consistent use of stainless steel and aluminium. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are available directly in our shop.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5

- High-quality letterbox pillar made of stainless steel and aluminium.
- Quality production - Made in Germany by Briefkasten Manufaktur Lippe.
- Letterbox (BH 400x400mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice.
- Innovative push-key lock with 2 keys.
- Mail is inserted and removed from the front. Insertion flap with high-quality axle dampers for very quiet mail insertion.
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 across, even large letters fit in here without creasing.
- Removal door opens from top to bottom. So the mail cannot fall towards you.
- Optional name labelling approx. 15-20 mm high.
- Optional house number labelling approx. 70-80mm high.
- Newspaper compartment (BH 400x200mm) made of stainless steel 1.4016 (stainless magnetic stainless steel), powder-coated in RAL of your choice with stainless steel laser inscription "ZEITUNG" (font ARIAL, if name/house number, then the same as your chosen font).
- Newspaper compartment can be opened from bottom to top.
- Functional box (BH 400x200mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL colour of your choice.
- Optimum rain protection thanks to rain guard edges and a rain roof made of 3mm aluminium AlMg3 W19, powder-coated in RAL of your choice.
- Side cladding made of 3 mm aluminium AlMg3 W19, powder-coated in RAL of your choice.
- Rear panel and base plate made of 6mm aluminium AlMg3 W19, powder-coated in RAL of your choice.
- Invisible fastening in the column thanks to reinforced base plate.
- Invisible cable feed through the body possible. The overall height is 1.65 m.
- **WITHOUT LOXONE intercom/system components!**

Important information

Camera or call station preparation

We recommend that the electrical installation is always carried out by an electrician.

We offer the preparation of intercom stations from various manufacturers for our letterboxes. The preparation does not include any end devices, but only the provision of screw mounts, drill holes and perforations. This means that you can install your end device without any problems.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Product properties

| | |
|---|--|
| Surface/colour | RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white |
| Series | GOETHE |
| Functions | Newspaper compartment, Camera, Intercom, Fingerprint, Keypad |
| Functional box prepared for manufacturer | LOXONE |
| Material | Aluminium AlMg3 W19, Stainless steel V2A 1.4301, Stainless steel 1.4016 (non-rusting magnetic stainless steel) |
| Mounting type | Free-standing |
| House number | House number as laser engraving |
| Name labelling | Laser-engraved |
| Removal of mail | On the front |
| Number of letterboxes | with 1 letterbox |
| Boxes by volume | Large > 16 litres |

Abmessungen

| | |
|---|---|
| Height of single box in mm: | BK 400.0 ZF 200.0 |
| Width of single box in mm: | 400,0 |
| Capacity in litres: | BK 16.0 ZF 8.0 |
| Height of letterbox slot in mm: | 35,0 |
| Width of letter slot in mm: | 360,0 |
| Height of letterbox in mm: | 800,0 |
| Width of letterbox system in mm: | 400,0 |
| Overall height in mm: | 1614,0 |
| Total width in mm: | 408,0 |
| Depth in mm: | 100.0 + 25.0 Rain roof |
| Weight in kg: | 46 |
| Delivery condition: | Delivery is assembled |
| Shipping information: | Delivery by haulage company on a one-way pallet. Before delivery, the forwarding agent will contact you by telephone to arrange an appointment. |

More images





