

2-piece surface-mounted letterbox design BASIC 382A AP with bell box - RAL 7016 anthracite grey | RAL 7016 anthracite grey, fine structure, matt | 150mm depth | with 2 letterboxes (1x2) | Top

Product number 382A-7016-2-SP-150-O



Product description

2-post surface-mounted letterbox design BASIC 382A AP with bell box - RAL 7016 anthracite grey

High-quality stainless steel surface-mounted letterbox for 2 parties made in Germany by Briefkasten Manufaktur.

The complete surface-mounted letterbox system is made of galvanised steel, powder-coated in RAL 7016 anthracite grey. The very high-quality workmanship and the well thought-out concept make this letterbox system our top seller. A rain drainage edge for optimum water protection, a double-edged throw-in flap with rubber bumper, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this surface-mounted letterbox system.

Thanks to the design, self-assembly is straightforward.

- · 2-piece surface-mounted letter box made of galvanised steel, powder-coated in RAL 7016 anthracite grey
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with noise-absorbing rubber buffers for very quiet insertion of mail.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder for each letterbox.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- Incl. side panelling + rain cover in solid design.
- For wall mounting incl. fixing material (screws + dowels).
- · Intercom bell part made of galvanised steel, powder-coated in RAL 7016 anthracite grey
- Speech perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- 2x round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.



Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water may still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Material Steel, galvanised

Series BASIC

Number of bell push buttons 1 button, 2 buttons, 3 buttons

Functions Light button, Intercom

Functional box prepared for GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner,

manufacturer Auerswald, Legrand Bticino, Comelit

Name labelling Nameplate

Surface/colour RAL 7016 anthracite grey

Number of boxeswith 2 letterboxesRemoval of mailOn the frontBoxes by volumeLarge > 16 litresMounting typeSurface-mounted

Dimensions

Height of single box in mm 330,0
Width of single box in mm 355,0
Capacity in litres 12,0 | 17,0
Height of letterbox slot in mm 35,0
Width of letter slot in mm 325,0
Height of letterbox in mm 760,0
Width of letterbox system in mm 355,0
Depth in mm 100,0 | 150,0

Weight in kg 12



More images







