

Designer doorbell pedestal - polished V2A stainless steel with 2N Verso - 2N Solo prepared | without | 2N Verso/Solo 1-way prepared | 160 cm | Stainless steel, ground

Product number 870-VA-2N-1FACH-160



Product description

Designer doorbell pillar - V2A stainless steel, polished, prepared with 2N Verso - 2N Solo

High-quality doorbell pillar made entirely of V2A stainless steel, polished, from Briefkasten Manufaktur. This doorbell pillar is suitable for the integration of the 2N IP VERSO, 2N IP SOLO and 2N LTE VERSO models in flush-mounted design. The 2N video intercom can be seamlessly integrated into the flush-mounted design and replaced at any time. Our products have a high quality, reliable functionality and a unique identity. Made by Briefkasten Manufaktur.

- Doorbell pillar made of 1.5 mm stainless steel V2A 1.4301, 240 grain polished.
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The speech part is made of 2 mm stainless steel V2A 1.4301, polished. Dimensions: W 190 mm x H 640 mm x D 110 mm.
- Incl. 6x screw cover caps made of V2A stainless steel, polished, so that the screws for fastening the front panel are not visible. See pictures.
- The fully welded pedestal is made of 1.5 mm stainless steel V2A 1.4301, polished. Construction height is either 1.30 m or 1.60 m.
- The pedestal is fitted with a VA base plate. This is 10 mm thick and is finished with a cover plate. See pictures.
- Invisible cable feed through the body is possible.
- **The preparation is intended for 1-3 2N modules. WITHOUT 2N system components!**

Important information

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is completely placed in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Series	GRIMM
Functions	Camera, Intercom
Functional box prepared for manufacturer	2N
Mounting type	Free-standing
Material	Stainless steel V2A 1.4301
Surface/colour	Brushed

Dimensions

Height of single box in mm	640,0
Width of single box in mm	190,0
Overall height in mm	1300,0 1600,0
Total width in mm	220.0 (foot plate 320.0)
Depth in mm	110.0 (foot plate 210.0)
Weight in kg	40
Delivery condition	Delivery is assembled

Drawing



More images



