

# Stainless steel doorbell pedestal Designer - RAL of your choice - GIRA System 106 - 3-gang prepared | without | Gira System 106 1x3 prepared | 130 cm | ? Colour of your choice

Product number 870-VAR-V-3XGI106-130



### Product description

# Stainless steel doorbell pillar designer - RAL of your choice - GIRA System 106 - 3-gang prepared

High-quality doorbell pillar from the Briefkasten Manufaktur brand. The Gira System 106 can be used seamlessly in a flush-mounted design. The preparation is intended for 3 GIRA 106 system modules. The modules can be flush-mounted using the simple mounting system (surface-mounted housing 5503910 required!).

This is a real eye-catcher among the technical pedestals. Clear lines and no-frills design characterise the designer collection with GIRA System 106. Our products have a high quality, reliable functionality and their own identity. Made by Briefkasten Manufaktur.

- Doorbell pillar made of 1.5 mm stainless steel V2A, powder-coated in RAL colour.
- The speech part is made of 2 mm stainless steel V2A 1.4301, powder-coated in RAL colour. Dimensions: W 190 mm x H 640 mm x D 110 mm.
- Incl. 6x screw cover caps made of V2A stainless steel, polished so that the screws for fastening the front panel are not visible. See pictures
- The fully welded pedestal is made of 1.5 mm V2A stainless steel, powder-coated. Construction height is either 1.30 m or 1.60 m.
- The pedestal is equipped with a VA base plate. This is 10 mm thick and is finished with a cover plate. See pictures.
- Invisible cable feed through the body possible.
- WITHOUT GIRA system components!

#### Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. In certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.



## **Product properties**

Surface/colour RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of

your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white

**Series GRIMM** 

Camera, Intercom **Functions** 

Functional box prepared for

manufacturer

Free-standing

**GIRA** 

Mounting type Material Stainless steel V2A 1.4301

#### **Dimensions**

Height of single box in mm 640,0 Width of single box in mm 190,0

Overall height in mm 1300,0 | 1600,0


Total width in mm 220.0 (foot plate 320.0) Depth in mm 110.0 (foot plate 210.0)

Weight in kg

**Delivery condition** Delivery is assembled



#### Drawing





# More images







