

Gira surface-mounted home station pure white satin finish 125027 | Pure white silk matt

Product number 1250.4



Product description

Surface-mounted home station

Hands-free home station as a pre-assembled unit for surface mounting.

- Completely pre-assembled surface-mounted home station for quick and clean installation.
- Design diversity through integration into the switch programme, resulting in a uniform appearance of door communication and electrical installation.
- Installation both with and without cover frame.
- Simple installation thanks to plug-in screw terminals on the mounting plate. The contact to the home station is made when the home station is plugged onto the mounting plate.
- Easy removal of the home station during renovation work.
- Fastening holes for mounting.
- Signal transmission and power supply to the home station via reverse polarity protected and short-circuit proof 2-wire bus.
- Parallel connection of up to three home stations possible (with power supply via 2-wire bus).
- One-man commissioning thanks to simple commissioning procedure.
- Ring tone differentiation between door call, internal call and storey call.
- Choice of five different ring tone melodies that can be individually assigned to individual call buttons.
- Hands-free function (voice-controlled intercom with echo and background noise suppression).
- Enforcement function for loud ambient noise during the voice connection.
- With call blocking.
- Operating buttons with integrated LEDs for status display.

The operating buttons of the surface-mounted home station control the following functions in conjunction with the switching actuator or the flush-mounted switching actuator:

- Switching of light and other functions.
- Activation of the door opener.
- Setting the ring tone melody.
- Switching the ring tone on and off.
- Call acceptance.
- Activating the assertion function.
- Setting the ring tone and speech volume.

Technical data

Power supply: 26 V DC ± 2 V (bus voltage)

Connections:

2 screw terminals 2-wire bus

2 screw terminals Storey call button

Temperature range: -5 °C to +50 °C

Notes

- Installation without cover frame possible.
- A 2-gang cover frame without centre bar is required for installation with System 55 or the switch ranges FI¨chenschalter and E22.
- A cover frame is required for mounting on a device box
- This component can be used to set up telecommunications systems with up to 70 users
(e.g. 1 x built-in loudspeaker, 5 x extension module for built-in loudspeaker, 68 x surface-mounted home station).

Product properties

Connection technology 2-wire

Mounting type Surface-mounted

Dimensions

Width in mm 55
Height in mm 127
Depth in mm 20,0
Weight in kg 1