

# 1 surface-mounted letterbox BASIC Plus 382X AP with bell box on the side - RAL of your choice | Right | 100mm depth | ? Colour of your choice | with 1 letterbox

Product number 382XA-1W-SP-RAL-100-R



# Product description

# 1 surface-mounted letterbox BASIC Plus 592 AP with bell box on the side - RAL of your choice

German quality production "Made in Germany" by Briefkasten Manufaktur. The complete surface-mounted letterbox is made of weather-resistant stainless steel V2A, powder-coated in RAL colour. This stainless steel letter box is characterised by a rain drainage edge for optimum water protection, a double-edged throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- Single surface-mounted letterbox made of high-quality, weather-resistant stainless steel V2 A 1.4301, powder-coated in RAL colour
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with noise-absorbing rubber buffers for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes
- Bell box made of stainless steel V2A 1.4301, powder-coated in RAL colour
- Speech perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in the scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Incl. close-fitting side cladding + rain cover made of V2A stainless steel, powder-coated in RAL colour.
- For wall mounting incl. fixing material.

#### Important information

#### Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.



#### Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water may still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

### Product properties

Surface/colour RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of

your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white

**Series BASIC** 

Number of bell push

**buttons** 

**Functions** 

1 button, 2 buttons, 3 buttons

Functional box prepared for manufacturer

GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald,

Legrand Bticino, Comelit

Light button, Intercom

Normal > 10 litres Boxes by volume

Name labelling Nameplate

Material Stainless steel V2A 1.4301

330.0

355,0

House number House number as laser engraving

Removal of mail On the front **Number of letterboxes** with 1 letterbox Mounting type Surface-mounted

# Abmessungen

Height of single box in

mm:

Width of single box in

mm:

12,0 | 17,0 Capacity in litres:

Height of letterbox slot 35,0

in mm:

Width of letter slot in 325,0

mm:

Height of letterbox in

mm:

330.0

Width of letterbox

system in mm:

525,0

12

Depth in mm: 100,0 | 150,0 Weight in kg:

**Shipping information:** 

Depending on the order volume, delivery will be by parcel post or bulky goods. Partial deliveries are

possible for dismountable products (e.g. stand mailboxes can be shipped separately).



# More images





















