

COMELIT IP home station video 6742W with mobile function

Product number 1299-6742W



Product description

COMELIT IP home station video 6742W with mobile function

Colour monitor with 4.3" screen 16/9, full-duplex hands-free function and touch-sensitive buttons. Control of brightness, colour and volume of the ringtone, which can be individually selected from various melodies. Equipped as standard with buttons for door opener, with corresponding LED display, as well as 7 additional soft-touch buttons for call acceptance, self-activation, call to porter control centre, ring tone deactivation, menu call and menu control. Manages the storey call as standard. The equipment includes the base plate for wall mounting or for mounting on housings for the living area. Power supply via PoE and connection to the VIP system via RJ45 plug. Dimensions: 160x115x22mm.

This version of the is equipped with an integrated Wifi system. After installing the system and the free app for your smartphone (Apple iOS or Android), you can connect the two in just a few very simple steps. This also requires a one-off registration with the Comelit cloud. You can then access your indoor intercom from anywhere in the world. The image and sound are transmitted smoothly and in high quality. Both communication and opening the front door or gateway are possible via the app. The app also allows you to manage the video intercom system and other advanced functions via the 3G network or higher networks.

With the 6742W door station and the Comelit app, you can simulate a domestic presence, no matter where you are. If a neighbour, postman or stranger rings the doorbell, you answer the door call with your smartphone or tablet and give the visitor at the door the feeling that you are at home, even if you convince them with an excuse that you cannot come to the door at the moment (we are bathing the children; I am expecting visitors and am changing my clothes; I have just got out of the shower...). When a door call is made, it is sent from the Mini WiFi indoor intercom to the Comelit Cloud via the WiFi router and forwarded to the smartphone or tablet (a 3G / LTE data connection is required). Due to the unique technology of IP technology in conjunction with a WiFi monitor, the time delay for reception in the 3G network on the mobile device is only approx. 5 seconds. The mobile device opens the app even when it is closed: the push function makes this possible.

The VIP system is the evolution of video intercom systems and the associated services. The services fulfil all modern requirements of buildings used for residential, commercial, industrial and industrial-related service providers: from single-family homes to building complexes, both new buildings and conversions or renovations of old buildings. It is designed to connect an unlimited number of subscribers and allows simultaneous calls without distance restrictions. The devices are connected to a single, dedicated or existing network via RJ45. In the ViP system, all devices are connected to the (dedicated or shared) LAN network, from the external station to the most remote internal station. Compared to traditional analogue video intercom systems, the digital network protocol makes it easy to configure the system without costly or complex measures, and even system updates are extremely versatile and practical. Installation, commissioning and reconfiguration can be carried out easily and completely securely in the network.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, fitting and installation.

Product properties

Connection technology LAN

Dimensions

Width in mm 160

Height in mm 115

Depth in mm 20,0

Weight in kg 1

More images

