

IP video module Ultra (without button cover) - RAL of your choice

Product number 1299-KSUT8020-HB-MP-OT



Product description

IP video module Ultra - RAL colour of your choice

- Audio/video unit in RAL/DB colour of your choice.
- IP system, simply plug in the LAN cable and get started.
- Wide-angle camera (H160° x V100° field of view) with HD resolution.
- LED illumination of the camera. Thanks to the integrated infrared LEDs under the camera lens, all visitors are optimally displayed even at night.
- Omnidirectional digital microphone and two loudspeakers for hi-fi audio.
- Additional visual and acoustic indicators for disabled persons, adjustable in the programming.
- Thanks to the 2 integrated relays, door or gate openers can be connected directly via the module. The 2 door and gate openers are controlled via the indoor station or via your smartphone or tablet using an app.
- Protection class IP65 and IK08.
- Module for rear installation in our panels and letterbox systems.
- Optional accessories required (see accessories): Button cover, Ultra 3063U push-button interface (for external buttons), 1440 switch, 1441 PoE power supply unit, Ultra digital call module, Ultra touchscreen module, 6742W, 6722W, 6842W or 6802W home station video.
- Recommended installation height: 1350-1600mm.

The ViP system is the evolution of video intercom systems and the associated services. The services fulfil all modern requirements of buildings used for residential, commercial, industrial and industrial-related service providers: from single-family homes to building complexes, both new buildings and conversions or renovations of old buildings. It is designed to connect an unlimited number of subscribers and allows simultaneous calls without distance restrictions. The devices are connected to a single, dedicated or existing network via RJ45. In the ViP system, all devices are connected to the (dedicated or shared) LAN network, from the external station to the most remote internal station. Compared to traditional analogue video intercom systems, the digital network protocol makes it easy to configure the system without costly or complex measures, and even system updates are extremely versatile and practical. Installation, commissioning and reconfiguration can be carried out easily and completely securely in the network.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, fitting and installation.

Product properties

Surface/colour	RAL 9005 deep black, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white
Mounting type	Rear construction
Connection technology	LAN
Material	Aluminium AlMg3 W19

Dimensions

Width in mm	Outdoor station 100 Power supply unit 141
Height in mm	Front-door station 90 Power supply unit 89
Depth in mm	Front-door station 35.0 Power supply unit 62.0
Weight in kg	2
Delivery condition	Delivery is assembled

More images

