

# Gira System 106 door station module with commissioning button - stainless steel V2A | Stainless steel, ground

Product number S106-5569920-VA



## Product description

### Gira System 106 door station module with commissioning button

**ATTENTION without button! See necessary accessories!**

Compact voice module with call button prepared for communication between inside and outside. A high-quality microphone and a weatherproof loudspeaker ensure good communication. Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module). All other System 106 modules (except voice module) are supplied with power via the door station module.

The Gira System 106 is an installation system made of real metal in a purist, elegant design without a frame, based on a basic dimension of 106.5 × 106.5 mm. With the modular door station in the Gira System 106, hospitality begins at the front door. From the call button, voice and camera module to the info and dummy module, all functions are presented in a harmonious overall picture. In the dark, the backlit call buttons with labelling field ensure good legibility and an attractive appearance.

System 106 can be used in detached houses and apartment blocks, as well as in office buildings, industrial premises and hotels. The modular structure allows the system to be customised in size, design and functionality to suit individual requirements. Extensions and changes can be easily made at any time by exchanging modules. Even a pure front change is possible with the system. This means that the appearance of the system can be subsequently changed from, for example, traffic white to a stainless steel finish without having to replace the electronic units.

### Simple installation and step-by-step assembly

The system can be installed in various stages in parallel with the construction progress. For example, it is possible to install only the lower part of the surface-mounted housing first during shell construction, and then add cables and modules when they are needed.

## Technical data

### Power supply

System: via ribbon cable, 10-pin

2-wire bus: via control unit or via ZV (DC 24 V 300 mA)

### Power consumption

Maximum: 1 W

Stand-by mode: 240 mW

### Connections

2-wire bus: 1 x plug-in terminal

ZV: 1 x plug-in terminal

System: 2 x connector strip

Video (analogue): 1 x connector strip

**Ambient temperature:** -25 °C to +70 °C

**Protection class:** IP54

## Product properties

**Connection technology** 2-wire

**Material** Stainless steel V2A 1.4301

**Surface/colour** Brushed

## Dimensions

**Width in mm** 106,5

**Height in mm** 106,5

**Depth in mm** 20,0

**Weight in kg** 1

## More images





