

elo 43 inch Open Frame Touchscreen 4363L

Product number 611-4363L



Product description

elo 43-inch open frame touchscreen

The 4363L 43-inch full HD open frame from Elo with its ultra-modern slim format enables easy integration into enclosures and kiosks. From self-order and self-checkout kiosks to industrial controls, plant room control panels and wayfinding solutions, Elo's commercial interactive displays offer the versatility to add touch capabilities to your solution.

Designed for easy integration, mount the 4363L touchscreen monitor in landscape, portrait or reclining format for optimal flexibility when integrating into any counter, kiosk or cabinet design.

Place your touchscreen behind an extra layer of protection: For installations requiring specific IP ratings or protection from vandalism and demanding environments, Elo TouchPro PCAP displays offer excellent touch response with capacitive reactance. Capacitive responsive touch allows the display to be mounted behind a glass front up to 6mm thick or a plastic front up to 3mm thick to create a fully enclosed kiosk.

Brilliant, interactive TouchPro® PCAP display: The 63 Series offers anti-glare or anti-friction models with borderless glass and up to 40 simultaneous touches for an enhanced, tablet-like experience.

NEW at a %SPECIAL PRICE%

Technical specifications

Case colour:	Black
Contrast ratio:	4000:1
Screen diagonal:	42.5 inch diagonal, active matrix TFT LCD (LED)
Active area:	37.04" x 20.84" / 940.86 mm x 529.254 mm
Surface treatment:	Anti-friction
Touch user interface:	USB
Bezel:	Without bezel
Brightness (typical):	LCD panel: 450 cd/m ² TouchPro PCAP: 387 cd/m ²
Colours:	8-bit (16.7 million)
Resolution:	1920 x 1080 @ 60hz
Total response time (typical):	8 msec
Input voltage:	100-240 VAC, 50/60 Hz
Power consumption (typical):	ON (monitor + AC/DC adaptor): 51 W OFF (monitor + AC/DC adaptor): 0.61 W OFF (monitor + AC/DC adaptor): 0.20 W
Operating temperature:	Portrait/landscape: 0°C to 40°C / 32°F to 104°F Desktop: 0° C to 35° C / 32°F to 95°F
Storage temperature:	Portrait/landscape: -20°C to 60°C / -4°F to 140°F Desktop: -20° C to 60° C / -4° F to 140° F
Humidity:	Operating: 20% to 80% Storage: 10% to 90% (38.7° max. wet bulb thermometer temperature)
MTBF:	50,000 hours, proven

Dimensions

Width in mm	999,3
Height in mm	587,5
Depth in mm	66,2
Weight in kg	10,2