

Set of 3 GIRA System 106 - Stainless steel V2A - Camera intercom with 4x bell push-buttons | Stainless steel, ground

Product number S106-KS3V4-VA



Product description

Set of 3 GIRA System 106 - Stainless steel V2A - Camera intercom with 2x bell push-buttons

Gira System 106 made of V2A stainless steel in flush-mounted design for use in the DESIGNER 3-gang letterboxes or for simple surface mounting on the wall. 3 GIRA system modules and surface-mounted housing are included, so the system can be used directly in the letterbox. The system modules can be subsequently replaced as required thanks to the simple mounting system. The matching GIRA home station and control unit are available under accessories.

Surface-mounted housing 3gang Gira System 106 - 5503 910

- For flush-mounted installation of the modules.

Camera module Gira System 106 - 5561 000

- A high-quality camera with high light sensitivity is concealed behind the replaceable black glass pane. Thanks to a detection angle of 100°, the user is always aware of what is happening outside his front door.

Call button module Gira System 106 - 5539 000

- With 4 commissioning buttons for step-by-step installation.
- 4x call button with labelling field 5547920.

Voice module Gira System 106 - 5563 920

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with power via the door station module.

Additional components required. See accessories!

- Gira surface-mounted home station video plus 1239xx or Gira surface-mounted home station video 7 1209xx
- Gira video REG control device

Important information

Camera or intercom station preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, fitting and installation.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Product properties

Connection technology	2-wire
Material	Stainless steel V2A 1.4301
Surface/colour	Brushed

Dimensions

Width in mm	320
Height in mm	106
Depth in mm	20,0

More images

