

# 4-piece stainless steel surface-mounted letterbox BASIC Plus 382X AP with bell box on the side | Left | 100mm depth | with 4 letterboxes (2x2) | Stainless steel, ground

Product number 382XA-VA-4W-SP-100-L



## Product description

# 4-piece stainless steel surface-mounted letterbox BASIC Plus 382X AP with bell box on the side

German quality production "Made in Germany" by Briefkasten Manufaktur. The complete 3-piece surface-mounted letterbox is made of weather-resistant V2A stainless steel, polished. This stainless steel letter box is characterised by a rain drainage edge for optimum water protection, a double-edged throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

Thanks to the design, self-assembly is uncomplicated. The letterbox system is prepared for uncomplicated complete assembly, so there is no need for time-consuming wall mounting of individual boxes.

- · 4-piece surface-mounted letterbox made of high-quality, weather-resistant stainless steel V2 A 1.4301, polished
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with noise-absorbing rubber buffers for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, changeable name plate under the flap and post holder.
- Large capacity thanks to optional letterbox depth +50 mm = approx. 17 litres. Suitable for companies and households with very high mail volumes.
- Bell box made of stainless steel V2A 1.4301, polished
- Intercom hole with universal adapter. (Intercom system/ built-in loudspeaker not included in the scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Incl. close-fitting side panelling + rain cover made of V2A stainless steel, polished.
- For wall mounting incl. mounting rail and fixing material (screws + dowels).

### Important information

Camera or intercom preparation



The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

#### Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

# **Product properties**

**BASIC Series** Number of bell push buttons 4 buttons

**Functions** Light button, Intercom

Functional box prepared for GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner,

manufacturer Auerswald, Legrand Bticino, Comelit

Boxes by volume Normal > 10 litres **Number of boxes** with 4 letterboxes

Name labelling Nameplate

Material Stainless steel V2A 1.4301

Removal of mail On the front Surface/colour Brushed

Mounting type Surface-mounted

#### **Dimensions**

Height of single box in mm 330,0 Width of single box in mm 355,0 Capacity in litres 12,0 | 17,0 Height of letterbox slot in mm 35,0 Width of letter slot in mm 325,0 Height of letterbox in mm 660,0 Width of letterbox system in mm 880,0

Depth in mm 100,0 | 150,0

Weight in kg 12



# More images





















