

Design flush-mounted letterbox GOETHE UP - RAL of your choice - Doorbell intercom box - INDIVIDUAL | without newspaper compartment | Individual preparation

Product number 215-UP-1-SP-IND



Product description

Design flush-mounted letterbox GOETHE UP - RAL of your choice - bell and intercom box

High-quality flush-mounted letterbox with bell/intercom box in flush-mounted design. The modern GOETHE letterbox is ideal for the sophisticated entrance area. The linear design without a visible lock makes this letterbox look particularly elegant. The individually configurable bell intercom box is available with a flush-mounted bell button, a nameplate or labelling in combination with your desired intercom preparation (built-in loudspeaker not included) and/or camera preparation.

The dimensions of the single box allow a capacity of approx. 16 litres, the large insertion slot guarantees no crumpled mail even with DIN C4 envelopes and magazines or after several days of absence. The innovative push-key lock is concealed inside the letterbox. The key is simply inserted into the existing opening (no turning required) and the door opens. With the arrangement of the lock, this letterbox is designed in such a way that the removal door prevents the mail from falling towards you. The water drainage edge ensures that the mail inside is optimally protected from the weather. The insertion flap is fitted with high-quality axle dampers, guaranteeing quiet closing and preventing annoying rattling caused by the weather.

The letterbox systems in the GOETHE collection are characterised by the consistent use of stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are available directly in our shop.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5



- Flush-mounted letterbox made entirely of stainless steel.
- Quality production Made in Germany by Briefkasten Manufaktur Lippe.
- Letterbox (BH 400x400mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL of your choice.
- Innovative push-key lock with 2 keys.
- Mail is inserted and removed from the front. Insertion flap with high-quality axle dampers for very quiet mail insertion.
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 across, even large letters fit in here without creasing.
- Removal door opens from top to bottom. So the mail cannot fall towards you.
- Optional house number labelling approx. 70-80 mm high.
- Functional box (BH 400x200mm) made of stainless steel 1.4016 (non-rusting magnetic stainless steel), powder-coated in RAL colour of your choice.
- Choice of replaceable stainless steel nameplate with laser inscription, Plexi nameplate or illuminated direct inscription.
- 8-12V DC short-stroke bell push with LED ring lighting (blue, white, red or green). The bell button lighting cannot be supplied via the control unit. It must be connected to an additional 8-12 V DC power supply.
- An 8-12 V DC short-stroke light button with pictogram is available as an option.
- Preparation (built-in loudspeaker not included) for intercom system possible.
- Optionally with universal adapter for all commercially available built-in loudspeakers.
- Optional preparation (camera not included in scope of delivery) for a camera.
- Optimum rain protection thanks to rain guard edges.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, powder-coated in RAL colour.

Important information

Camera or call station preparation

We recommend that the electrical installation is always carried out by an electrician.

We offer the preparation of intercom stations from various manufacturers for our letterboxes. The preparation does not include any end devices, but only the provision of screw mounts, drill holes and perforations. This means that you can install your end device without any problems.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.

Product properties

Surface/colour RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of

your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white

Series GOETHE
Number of bell push 1 button

buttons Functions

Light button, Camera, Intercom, Fingerprint, Keypad

Functional box prepared for GIRA, Busch Jaeger, Siedle, STR Elektronik, ELCOM, TCS, Ritto, ALGO, Telegärtner, Auerswald, manufacturer Legrand Bticino, HHG, HIKVISION, PCS, Sesam, ekey, Comelit, Schneider Intercom / COMMEND

Name labelling Laser-cut engraving, Nameplate, Laser-engraved, Illuminated laser-cut engraving

Material Stainless steel V2A 1.4301, Stainless steel 1.4016 (non-rusting magnetic stainless steel)

House number House number as laser engraving

Removal of mail

Number of boxes

Boxes by volume

Mounting type

On the front

with 1 letterbox

Large > 16 litres

Flush-mounted

Briefkasten Manufaktur Lippe GmbH Werler Straße 60 32105 Bad Salzuflen www.briefkasten-manufaktur.de info@briefkasten-manufaktur.de Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck Ust.ID.Nr. DE303690847

Handelsregister Amtsgericht Lemgo, HRB 8618



Dimensions

Height of single box in mm BK 400,0 | FK 200,0

Width of single box in mm 400,0 Capacity in litres 16 Height of letterbox slot in mm 35,0 Width of letter slot in mm 360,0

Height of letterbox in mm Außenmaß 652,0 | Einbaumaß 610,0 Width of letterbox system in mm Außenmaß 452,0 | Einbaumaß 410,0

Total width in mm 408,0


Depth in mm 100,0 | Einbaumaß 103,5


Weight in kg 12


Delivery condition Lieferung erfolgt montiert



Drawing









More images





















