

Set of 2 GIRA System 106 - Stainless steel V2A, powder-coated RAL 7016 fine structure - Camera intercom with 1x bell push-button | RAL 7016 anthracite grey, fine structure, matt

Product number S106-KS2V1-7016



## Product description

# Set of 2 GIRA System 106 - Stainless steel V2A - Camera intercom with 1x bell pushbutton

Gira System 106 made of V2A stainless steel in flush-mounted design prepared for use in the DESIGNER 2-gang letterboxes or for simple surface mounting on the wall. 2 GIRA system modules and surface-mounted housing are included, so the system can be used directly in the letterbox. The system modules can be subsequently replaced as required thanks to the simple mounting system. The matching GIRA home station and control unit are available under accessories.

#### Surface-mounted housing, 2-gang Gira System 106 - 5502 910

• For flush-mounted installation of the modules.

#### Camera module Gira System 106 - 5561 000

• A high-quality camera with high light sensitivity is concealed behind the replaceable black glass pane. Thanks to a detection angle of 100°, the user is always aware of what is happening in front of his front door.

#### Gira System 106 door station module - 5569 920 + call button 5549 920

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with power via the door station module.

## Additional components required. See accessories!

- Gira surface-mounted home station video plus 1239xx or Gira surface-mounted home station video 7 1209xx
- Gira video REG control device

### Important information

### Camera or intercom station preparation

The intercom systems must be connected by an electrician. Contact your trusted electrician for planning, fitting and installation.

#### Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. In certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Briefkasten Manufaktur Lippe GmbH Werler Straße 60 32105 Bad Salzuflen www.briefkasten-manufaktur.de info@briefkasten-manufaktur.de Tel.: +49 5222 807110

Geschäftsführer Oliver Woineck Ust.ID.Nr. DE303690847 Handelsregister Amtsgericht Lemgo, HRB 8618



# **Product properties**

Connection technology 2-wire

MaterialStainless steel V2A 1.4301Surface/colourRAL 7016 anthracite grey

## **Dimensions**

Width in mm 214 Height in mm 106 Depth in mm 20,0



# More images







