

GOETHE MDW design letterbox - RAL of your choice | 390-560mm depth

Product number 215-MDW-1IND-560



Product description

GOETHE MDW design mailbox - RAL of your choice

The modern GOETHE wall letterbox is ideal for the sophisticated entrance area. The linear design makes this letterbox look particularly elegant. Thanks to the variable shaft length between 300mm and 390mm or 390mm to 560mm, this letterbox can be used in almost all types of masonry.

The dimensions of the individual boxes allow a capacity of approx. 24-44 litres, and the large slot guarantees no crumpled mail, even with DIN C4 envelopes and magazines or after several days of absence. Thanks to the water drainage edge, the mail inside is optimally protected from the weather. The insertion flap is fitted with high-quality axle dampers, guaranteeing quiet closing and eliminating the annoying rattling caused by the weather.

The letterbox systems in the GOETHE collection are characterised by the consistent use of stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts for all GOETHE systems are available directly in our shop.

Thanks to the design, self-assembly is uncomplicated.

Protected utility model according to DPMA file number DE: 20 2021 101 679.5

- High-quality, stainless steel letterbox.
- Shaft made of 1.4016 stainless steel (magnetic stainless steel), bright.
- Body made of stainless steel 1.4016 (stainless magnetic stainless steel), powder-coated in RAL colour of your choice.
- Quality production - Made in Germany by Briefkasten Manufaktur Lippe.
- The letterbox complies with DIN/EN 13724. Insertion size (3.5 cm x 36.0 cm) for C4 landscape, large letters also fit in here without creasing.
- Letter slot & removal door made of stainless steel V2A 1.4301, powder-coated in RAL colour of your choice.
- Letters are inserted and removed from the front. Insertion flap with high-quality axle dampers for very quiet mail insertion.
- Removal door opens from top to bottom. This prevents the mail from falling towards you.
- Optional name labelling approx. 15-20 mm high.
- Optional house number labelling approx. 70-80mm high.
- Plaster cover frame made of stainless steel angle profile 25 x 58 mm, powder-coated in RAL colour.
- Variable shaft length 300-390mm or 390-560mm. External dimensions of letter slot W 380 mm x H 180 mm.
- External dimensions front and rear W 450mm x H 250mm.

Important information:

To achieve optimum water protection for your mail, the letter box or letter box system should be located under a canopy if possible.

The mail is only protected from water if it is completely placed in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to enter the letterbox. This system is protected against the ingress of water in accordance with DIN EN 13724. Water ingress is not a reason for complaint.


Product properties

Surface/colour	RAL 9005 deep black, RAL 3004 crimson red, DB 703 iron mica, RAL 7016 anthracite grey, RAL of your choice (according to colour table), RAL 9007 grey aluminium, RAL 9016 traffic white
Series	GOETHE
Material	Stainless steel V2A 1.4301, Stainless steel 1.4016 (non-rusting magnetic stainless steel)
House number	House number as laser engraving
Name labelling	Laser-engraved
Number of boxes	with 1 letterbox
Boxes by volume	Jumbo > 30 litres
Mounting type	Wall throw-through
Removal of mail	On the back

Dimensions

Height of single box in mm	200,0
Width of single box in mm	400,0
Capacity in litres	24,0 - 32,0 32,0 - 44,0
Height of letterbox slot in mm	35,0
Width of letter slot in mm	360,0
Total width in mm	450,0
Depth in mm	300,0 - 390,0 390,0 - 560,0
Weight in kg	16
Delivery condition	Supplied partially disassembled

Drawing



More images

