

DoorBird IP VIDEO home station A1101 | White

Product number 1298-A1101-WH



Product description

DoorBird IP VIDEO Home Station A1101 White Edition

The DoorBird IP Video indoor station is the ideal addition to any letterbox with DoorBird IP Video door station. It is characterised by outstanding video and audio quality. The compact and discreet design harmonises with any environment. The screen of the indoor station is made of scratch-resistant safety glass. The intuitive user interface with clear symbols means that all functions can be accessed in seconds. All main functions can be called up using the hardware buttons - without using the touchscreen.

The customised ringtone for the front door, floor or gate allows you to distinguish exactly where the visitor is ringing. The LED status bar on the underside of the indoor station lights up in freely selectable colours.

Added value through IP

- Door opening and lift call
- Visitor history (free cloud recording)
- Weather forecast
- Home and building automation control (IP, TCP, HTTPS, relay, etc.)
- Configuration worldwide via the DoorBird app

Intuitive user interface

- 4-inch true colour touch display
- Scratch-resistant Gorilla® safety glass

2-way audio

- HD audio, up to 102 dB
- Over 50 ringtones

Compact housing

- 5 hardware buttons for the main functions
- Configurable RGB LED status bar

Unlimited range

- Supports WLAN, Ethernet, PoE
- Suitable for multiple DoorBird IP video door stations

TECHNICAL DATA

Surface-mounted, table stand A8003 available separately

Power supply 15 - 48 V DC (max. 15 W) or Power over Ethernet (PoE 802.3af Mode-A)

Weight 336 g

Connections

- LAN/PoE (T+, T-, R+, R-)
- Digital input #1 (0 V, 0 A (NO)), e.g. for a storey call button
- Digital input #2, (0 V, 0 A (NO)), e.g. for a second storey call button
- Bi-stable latching switching relay #1, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- Bi-stable latching switching relay #2, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- Bi-stable latching switching relay #3, max. 24 V DC / AC, 1 ampere, e.g. for electric door opener or lift
- 15 - 48 V DC input (+, -), max. 15 W Power consumption 5 W

Approvals CE, FCC, IC, RoHS, IP50

Operating conditions 0 to +55°C / 32 to 131°F

Relative humidity 0 % to 85 % (non-condensing)

SYSTEM REQUIREMENTS

Mobile device Latest iOS on iPhone/iPad, latest Android on smartphone/tablet

Internet High-speed fixed network Broadband Internet connection, DSL, cable or fibre optic, no sockets or proxy server

Network Ethernet network, with DHCP

Supported door stations Any DoorBird IP video door station

DISPLAY

Dimensions 4" true colour LCD

Touch Yes, capacitive

Resolution 800 x 480 px

IPS Yes

AUDIO

Audio components Speaker and microphone, echo and noise cancellation (AEC, ANR)

Audio streaming two-way

NETWORK

Ethernet PoE 802.3af Mode-A

WLAN 802.11 b/g/n 2.4 GHz

INTEGRATED RADIO MODULES

WLAN 802.11 b/g/n 2.4 GHz

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Dimensions

Width in mm 115

Height in mm 185

Depth in mm 25,0

Weight in kg 0,4

More images

