

Design wall light KEPLER SMALL 225x395 - 2-sided - RAL of your choice - house number - street or name | ? Color a elegir

Número de artículo 633R-HSNS



Descripción del producto

Design wall light KEPLER SMALL 225x395 - 2-sided - RAL of your choice - house number - street or name

High-quality wall light for outdoor and indoor use made of stainless steel, powder-coated. This luminaire with warm white light colour has a light outlet on both the top and bottom. The ideal complement for our letterboxes in the RAL colour of your choice. The sign is made of high-quality stainless steel V2A 1.4301. Design ELEGANCE is discreet lettering in polished stainless steel. By removing the powder coating, the polished stainless steel becomes visible and offers a high and elegant contrast.

- The wall light is made of cast aluminium, stainless steel and opal glass.
- Integrated LED module 2 x LED 5.8 W incl. converter, direct connection 230V, 50Hz, light colour white, 3000°K.
- Protective conductor connection.
- Protection class IP 44 - splash-proof.
- CE mark of conformity.
- Sign made of 2mm stainless steel V2A 1.4301, powder-coated in RAL colour.
- Dimensions: 225 x 395 x 2 mm (W x H x D).
- Street name/name lettering, laser-cut approx. 20-30 mm wide depending on the number of characters.
- House number, laser-cut approx. 70-100 mm high depending on the number of characters.
- With cast aluminium mounting plate for fixing the light by inserting the supplied dowels into the masonry.
- 2 fixing holes 10x6 mm in the wall plate, vertical spacing 60mm, horizontal spacing 100mm, cable entry with cable grommet for connection cable max. 1.5mm², connection terminal 2x2.5mm².
- Manufactured by Gebrüder Albert GmbH & Co KG Leuchtenfabrik - Quality Made in Germany (Fröndenberg).

Installation:

The national and international electronic safety regulations must be observed for the installation and operation of this luminaire. Loosen the wall plate from the luminaire fitting using the four hexagon socket set screws, pull the mains connection cable through the existing cable grommet and screw the wall plate to the mounting base. Make the protective conductor connection and electrical connection to the terminal. Fix the luminaire fitting over the wall plate and tighten it against the wall plate using the four hexagon socket set screws.

Características del producto

Superficie/color	Negro intenso RAL 9005, DB 703 mineral de hierro micáceo, RAL 7016 gris antracita, RAL de su elección (según tabla de colores), Aluminio gris RAL 9007, RAL 9016 blanco tráfico
Clase de protección	IP44
Fuente de luz	2x LED, 5,8 vatios
Tipo de montaje	Clavija de enchufe, Tornillos
Serie	KEPLER
Material de base	Aluminio AlMg3 W19, Acero inoxidable V2A 1.4301
Número de casa	Número de casa grabado con láser
Etiquetado de nombres	Etiquetado de nombres como grabado láser
Clase de protección	I

Dimensiones

Anchura en mm	225
Altura en mm	395
Anchura total en mm	225
Profundidad en mm	108,0

Más imágenes



