

Stainless steel fence letterbox BASIC Plus 382XZ with bell box - polished stainless steel - removal from the rear | Abajo | Acero inoxidable pulido | con 1 buzón

Número de artículo 382XAZ-VA-1-SP-U



Descripción del producto

Stainless steel fence letterbox BASIC Plus 382XZ with bell box for intercom - polished stainless steel - rear removal

High-quality fence letterbox with bell box for intercom system (optional camera) from Briefkasten Manufaktur. The post is inserted from the front, residents can remove the post from the back. The letterbox can be attached to your fence using the optional bar mat attachment; if this is not selected, the letterbox should be fitted and perforated on site by your fence builder. The complete fence letterbox is made of stainless steel V2A 1.4301, 240 grain polished. This stainless steel letter box is characterised by a rain drainage edge for optimum water protection, a throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- **Fence letterbox made of stainless steel V2A 1.4301, 240 grain polished**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letter box complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with sound-absorbing rubber seal for very quiet mail insertion.
- The door can be opened from left to right.
- Incl. 2 keys with key number, interchangeable nameplate (type 2) under the flap and post holder.
- Incl. side panelling + rain cover made of stainless steel V2A 1.4301, 240 grain polished.
- **Intercom bell part made of stainless steel V2A 1.4301, 240 grain polished**
- Intercom perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Suitable for fence mounting, fixing holes must be drilled on site. Optionally with bar mat holder.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Características del producto

Serie	BÁSICO
Caja de funciones preparada para el fabricante	GIRA, Busch Jaeger, Siedle, STR Electrónica, ELCOM, TCS, Ritto, Telegärtner, Auerswald, Legrand Bticino, Comelite
Caja individual por volumen	Normal > 10 litros
Etiquetado de nombres	Placa de identificación
Material de base	Acero inoxidable V2A 1.4301
Número de casa	Número de casa grabado con láser
Tipo de montaje	Valla
Número de cajas	con 1 buzón
Superficie/color	Suelo
Retirada de artículos	Parte trasera

Dimensiones

Altura de la caja individual en mm	330,0
Anchura de la caja individual en mm	355,0
Volumen en litros	12
Altura de la ranura para letras en mm	35,0
Anchura de la ranura para letras en mm	325,0
Altura del sistema de buzón en mm	430,0
Anchura del sistema de buzón en mm	355,0
Profundidad en mm	100.0 + 24.0 Rain roof
Peso en kg	8

Más imágenes





