

# 2 x 1 stainless steel fence letterbox BASIC Plus 382XZ with bell box - removal from the rear | Centre | avec 2 boîtes aux lettres (1x2) | acier inoxydable, poli

Numéro de référence 382XAZ-VA-2S-SP-M



## Description du produit

### 2x1 stainless steel fence letter box BASIC Plus 382XZ with bell box for doorbell intercom system - polished stainless steel - rear removal

High-quality fence mailbox for 2 parties with bell box for intercom system (optional camera) from Briefkasten Manufaktur. Mail is inserted from the front, residents can remove the mail from the back. The letterbox can be attached to your fence using the optional bar mat fastening; if this is not selected, the letterbox should be fitted and perforated on site by your fence builder. The complete fence letterbox is made of weather-resistant stainless steel V2A 1.4301, 240 grain polished. A rain drainage edge for optimum water protection, a throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this stainless steel letterbox.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- **2-post fence letterbox made of stainless steel V2A 1.4301, 240 grain polished**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber seal for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, interchangeable nameplate (type 2) under the flap and post holder for each party.
- Incl. side panelling + rain cover made of V2A stainless steel, 240 grain polished.
- **Intercom bell part made of V2A stainless steel, 240 grain polished**
- Intercom hole with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Suitable for fence mounting, fixing holes must be drilled on site. Optionally with bar mat holder.

## Important information

Camera or intercom preparation

**The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.**

## Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## Caractéristiques du produit

<b>Série</b>	BASIC
<b>Boîte de fonctions préparée pour le fabricant</b>	GIRA, Busch Jaeger, Siedle, STR Électronique, ELCOM, TCS, Ritto, Telegärtner, Auerswald, Legrand Bticino, Comelit
<b>Caisses individuelles par volume</b>	Normal &gt; 10 litres
<b>Inscription du nom</b>	Badge d'identification
<b>Matériau de base</b>	Acier inoxydable V2A 1.4301
<b>Numéro de maison</b>	Numéro de maison en gravure laser
<b>Type de montage</b>	Clôture
<b>Nombre de boîtes</b>	avec 2 boîtes aux lettres
<b>Surface/couleur</b>	Meulé
<b>Prélèvement de poste</b>	Verso

## Dimensions

<b>Hauteur du caisson individuel en mm</b>	330,0
<b>Largeur du caisson individuel en mm</b>	355,0
<b>Volume en litres</b>	12
<b>Hauteur de la fente d'introduction du courrier en mm</b>	35,0
<b>Largeur de la fente d'introduction du courrier en mm</b>	325,0
<b>Hauteur de la boîte aux lettres en mm</b>	760,0
<b>Largeur de la boîte aux lettres en mm</b>	355,0
<b>Profondeur en mm</b>	100.0 + 24.0 Rain roof
<b>Poids en kg</b>	14
<b>État de livraison</b>	System is delivered pre-assembled/partially disassembled

## Plus d'images





