

Stainless steel letterbox pillar Designer BIG - RAL of your choice - Rear removal - GIRA System 106 - VIDEO complete set

Artikelnummer 599RB-R-KSVG106



Produktbeschreibung

Stainless steel letterbox pillar Designer BIG - RAL colour of your choice - rear removal - GIRA System 106 - VIDEO complete set

High-quality manufactured letterbox pillar with rear removal from the Briefkasten Manufaktur brand made of stainless steel, powder-coated in RAL colour. Seamlessly integrated Gira System 106 in flush-mounted design. 3 GIRA system modules are included, so the letterbox can be used directly. The matching GIRA home station and the control unit to complete this letterbox are included. The modules can be replaced at any time thanks to the simple mounting system.

This is a real eye-catcher among letterboxes. Clear lines and no-frills design characterise the designer letterbox with GIRA System 106. Our products have a high quality, reliable functionality and their own identity. Made by Briefkasten Manufaktur.

- The letterbox module is made of 2mm stainless steel V2A 1.4301, powder-coated in RAL colour.
- Rear mail removal door 240 mm x 300 mm, opens from top to bottom. Incl. 2 keys with key number.
- Mail slot from the front, dimensions: W 32 cm x H 6.3 cm, C4 landscape. Very large letters fit in here without creasing.
- **Now with built-in damping elements that allow the flap to close slowly and quietly.**
- The pedestals are fitted with modules that can be replaced at a later date.
- The fully welded pedestal is made of 2 mm stainless steel V2A 1.4301, powder-coated in RAL colour. The overall height is 1.70 metres.
- The pedestal is fitted with a VA base plate. This is 10 mm thick and is finished with a cover plate. See pictures.
- Invisible cable feed through the body is possible.
- Name plate made of stainless steel, powder-coated. Your name can be lasered onto the nameplate.
- Optionally with house number, lasered.
- Incl. GIRA home station & control unit enclosed, System 106 door station module, info module & camera module installed.

GIRA

Gira System 106 camera module - 5561 000, installed without wiring

- A high-quality camera with high light sensitivity is concealed behind the replaceable black glass pane. Thanks to a detection angle of 100°, the user is always aware of what is happening outside his front door.

Info module Gira System 106 - 5560 920, installed

- For house numbers that need to be clearly visible.

Door station module Gira System 106 - 5565 920, installed without wiring

- Compact voice module with integrated call button for communication between inside and outside.
- A high-quality microphone and a weatherproof loudspeaker ensure good communication.
- Power supply via 2-wire bus. Additional connection for ZV (e.g. necessary from 3rd camera module).
- All other System 106 modules (except voice module) are supplied with power via the door station module.

Surface-mounted home station Gira Video 7 1209xx, enclosed

- Video home station with a 17.78 cm (7") TFT colour display and convenient hands-free function for surface mounting or wall mounting with flush-mounted device box or cavity wall box. With the optional stand (see accessories) also suitable for placement on furniture. A 32 GB SD memory card is included for internal image storage. Full-surface glass front with touch functionality and tactile feedback.

Video REG control device Gira 128800, enclosed

- Control device for supplying the audio and video components of the Gira door communication bus.
- Supply of the reverse-polarity protected and short-circuit-proof 2-wire bus when using video components such as colour camera, TFT colour display.
- Up to 2 door stations with colour camera and 28 home stations with TFT colour display can be supplied via the video control device.
- A total of up to 15 colour cameras can be controlled by the video control device (5 video door stations and 10 DCS camera gateways), of which two door stations with colour camera can be supplied with power by the video control device. The other colour cameras must each be operated with their own power supply for door communication.
- Self-resetting electronic short-circuit and overload detection of the operating voltages and the bus connection.
- Buttons for system and door opener programming.
- LED status indicators for operation, overload, system programming and door opener programming.
- AC 12 V output for supplying power to a standard electric strike.
- Relay output for switching an electric strike with its own power supply.
- Door opener switching time continuously adjustable from 1 to 10 s.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

To achieve optimum water protection for your mail, the letterbox or letterbox system should be located under a canopy if possible.

The mail is only protected from water if it is fully inserted in the box and the flap is closed. Mail that is not fully inserted allows moisture and dirt to penetrate the letterbox. It is therefore necessary to plan sufficiently dimensioned letterboxes for the upcoming requirements. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Produkteigenschaften

Surface/couleur	RAL 9005 noir profond, RAL 3004 rouge pourpre, DB 703 fer micacé, RAL 7016 gris anthracite, RAL au choix (selon le tableau des couleurs), RAL 9007 aluminium gris, RAL 9016 blanc trafic
Série	DESIGNER
Technique de raccordement	2 fils
Nombre de boutons de sonnette	1 bouton-poussoir
Fonctions	Porte-journaux, Caméra, Poste d'interphonie
Boîte de fonctions préparée pour le fabricant	GIRA
Type de montage	Autonome
Matériau de base	Acier inoxydable V2A 1.4301
Numéro de maison	Numéro de maison en gravure laser
Inscription du nom	Inscription du nom en gravure laser
Nombre de boîtes aux lettres	avec 1 boîte aux lettres
Caisses individuelles par volume	Grand > 16 litres
Prélèvement de poste	Verso

Abmessungen

Hauteur du caisson individuel en mm:	710,0 750,0
Largeur du caisson individuel en mm:	410,0 450,0
Volume en litres:	31
Hauteur de la fente d'introduction du courrier en mm:	63,0
Largeur de la fente d'introduction du courrier en mm:	320,0
Hauteur de construction en mm:	1700,0
Largeur totale en mm:	490.0 (base plate 580.0)
Profondeur en mm:	150.0 (footplate 240.0)
Poids en kg:	65
État de livraison:	Delivery is assembled
Informations sur l'envoi:	Delivery by haulage company on a one-way pallet. Before delivery, the forwarding agent will contact you by telephone to arrange an appointment.

Weitere Bilder





