

## 2er 1x2 stainless steel fence letterbox BASIC Plus 382XZ with bell box - RAL of your choice - removal from the rear | con 2 letterbox (2x1) | ? Colore a scelta | Sotto

Codice articolo 382XAZ-2W-SP-U



### Descrizione del prodotto

#### 2er 1x2 stainless steel fence mailbox BASIC Plus 382XZ with bell box - RAL of your choice - removal from the back

High-quality fence letterbox with bell box for intercom system (optional camera) from Briefkasten Manufaktur. Mail is inserted from the front, residents can remove the mail from the back. The letterbox can be attached to your fence using the optional bar mat attachment, if this is not selected, the letterbox should be fitted and perforated by your fence builder. The complete fence letterbox is made of weather-resistant stainless steel V2A 1.4301, powder-coated in the RAL colour of your choice. A rain drainage edge for optimum water protection, a throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this stainless steel letterbox.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- **2x fence mailbox made of stainless steel V2A 1.4301, powder-coated in RAL colour**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letterboxes comply with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flaps with sound-absorbing rubber seal for very quiet mail insertion.
- The doors can be opened from left to right.
- Incl. 2 keys with key number, interchangeable name plate (type 2) under the flap and post holder for each party.
- Incl. side cladding + rain cover made of V2A stainless steel, powder-coated in RAL colour.
- **Intercom bell part made of V2A stainless steel, powder-coated in RAL colour**
- Intercom hole with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Suitable for fence mounting, fixing holes must be drilled on site. Optionally with bar mat holder.

### Important information

Camera or intercom preparation

**The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.**

## Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water may still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

## Caratteristiche del prodotto

|                                                           |                                                                                                                   |
|-----------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|
| <b>Serie</b>                                              | BASE                                                                                                              |
| <b>Scatola delle funzioni preparata per il produttore</b> | GIRA, Busch Jaeger, Siedle, Elettronica STR, ELCOM, TCS, Ritto, Telegärtner, Auerswald, Legrand Bticino, Comelite |
| <b>Scatola singola a volume</b>                           | Normale > 10 litri                                                                                                |
| <b>Etichettatura dei nomi</b>                             | Etichetta con il nome                                                                                             |
| <b>Materiale di base</b>                                  | Acciaio inox V2A 1.4301                                                                                           |
| <b>Numero civico</b>                                      | Numero civico come incisione laser                                                                                |
| <b>Tipo di montaggio</b>                                  | Recinzione                                                                                                        |
| <b>Numero di scatole</b>                                  | con 2 cassette per le lettere                                                                                     |
| <b>Superficie/colore</b>                                  | Terra                                                                                                             |
| <b>Ritiro dell'articolo</b>                               | Lato posteriore                                                                                                   |

## Dimensioni

|                                                               |                        |
|---------------------------------------------------------------|------------------------|
| <b>Altezza della singola scatola in mm</b>                    | 330,0                  |
| <b>Larghezza della singola scatola in mm</b>                  | 355,0                  |
| <b>Volume in litri</b>                                        | 12                     |
| <b>Altezza della fessura per le lettere in mm</b>             | 35,0                   |
| <b>Larghezza della fessura per le lettere in mm</b>           | 325,0                  |
| <b>Altezza del sistema di cassette per le lettere in mm</b>   | 430,0                  |
| <b>Larghezza del sistema di cassette per le lettere in mm</b> | 710.0 + 8.0 Panelling  |
| <b>Profondità in mm</b>                                       | 100.0 + 24.0 Rain roof |
| <b>Peso in kg</b>                                             | 12                     |

## Altre immagini







