

Stainless steel fence letterbox BASIC Plus 382XZ with bell box - polished stainless steel - removal from the rear | Powyżej | Stal nierdzewna, polerowana | z 1 skrzynką na listy

Numer artykułu 382XAZ-VA-1-SP-O



Opis produktu

Stainless steel fence letterbox BASIC Plus 382XZ with bell box for intercom - polished stainless steel - rear removal

High-quality fence letterbox with bell box for intercom system (optional camera) from Briefkasten Manufaktur. The post is inserted from the front, residents can remove the post from the back. The letterbox can be attached to your fence using the optional bar mat attachment, if this is not selected, the letterbox should be fitted and perforated by your fence builder. The complete fence letterbox is made of stainless steel V2A 1.4301, 240 grain polished. A rain drainage edge for optimum water protection, a throw-in flap with rubber buffer, the solid interchangeable nameplate, a practical post holder and the very robust lock characterise this stainless steel letterbox.

The letterbox systems in the BASIC Plus collection are characterised by the consistent use of V2A stainless steel. The result is a very long service life and sustainability. The design has been developed by our own engineers with a view to high flexibility and modularity, simple spare parts assembly and uncomplicated self-assembly. Spare parts are directly available for all BASIC Plus systems.

- **Fence letterbox made of stainless steel V2A 1.4301, 240 grain polished**
- The system is manufactured by Briefkasten Manufaktur. German quality production "Made in Germany".
- The letter box complies with DIN/EN 13724. Insertion size (3.5 cm x 32.5 cm) for C4 landscape, large letters also fit in here without creasing.
- Insertion flap with sound-absorbing rubber seal for very quiet insertion of mail.
- The door can be opened from left to right.
- Incl. 2 keys with key number, interchangeable nameplate (type 2) under the flap and post holder.
- Incl. side panelling + rain cover made of stainless steel V2A 1.4301, 240 grain polished.
- **Intercom bell part made of stainless steel V2A 1.4301, 240 grain polished**
- Intercom perforation with universal adapter. (Intercom system/ built-in loudspeaker not included in scope of delivery). Also available without speech perforation.
- Universal adapter is suitable for all commercially available built-in loudspeakers (Siedle, Ritto, TCS, Busch-Jäger, Gira, Legrand Bticino, ELCOM, Auerswald, Comelit and many more).
- Round stainless steel bell push button type: Grothe Protact, max. 24 V AC/DC, 1.5 A, IP 54 (pressure force limitation).
- Anti-vandalism - The nameplate is indentation-proof and impact-resistant, the plastic is flame-retardant.
- Suitable for fence mounting, fixing holes must be drilled on site. Optionally with bar mat holder.

Important information

Camera or intercom preparation

The intercom systems must be connected by an electrician. Please contact your trusted electrician for planning, fitting and installation.

Water protection

The mail is only protected against moisture and dirt when it is fully inserted and the flap is closed. Under certain extreme weather conditions, water can still enter (up to 1ccm according to DIN EN 13724). This is not a reason for complaint.

Właściwości produktu

Seria	PODSTAWOWY
Liczba przycisków dzwonka	1 przycisk, 2 przyciski, 3 przyciski
Skrzynka funkcyjna przygotowana dla producenta	GIRA, Busch Jaeger, Siedle, STR Electronics, ELCOM, TCS, Ritto, Telegärtner, Auerswald, Legrand Bticino, Comelite
Pojedyncze pudełko według objętości	Normalny > 10 litrów
Etykietowanie nazw	Identyfikator
Materiał bazowy	Stal nierdzewna V2A 1.4301
Numer domu	Numer domu jako grawer laserowy
Typ montażu	Ogrodzenie
Liczba pudełek	z 1 skrzynką na listy
Powierzchnia/kolor	Uziemienie
Wycofanie przedmiotu	Tylna strona

Wymiary

Wysokość pojedynczego pudełka w mm	330,0
Szerokość pojedynczego pudełka w mm	355,0
Pojemność w litrach	12
Wysokość szczeliny na listy w mm	35,0
Szerokość szczeliny na listy w mm	325,0
Wysokość skrzynki na listy w mm	430,0
Szerokość skrzynki na listy w mm	355,0
Głębokość w mm	100.0 + 24.0 Rain roof
Waga w kg	8

Wi?cej zdj??





